



# Levo Series

## Code Blue Timers

When every second counts during a Code Blue event, your team needs to be able to rely on the accuracy of the clocks in every department. The Levo Series Code Blue Timer is a multi-function digital clock and timer that integrates with the existing facility Code Blue system to effectively time each event. Part of the Primex XR Series Time Synchronization system, the timer provides precise Code Blue event timing to help your team stay within recommended treatment guidelines and deliver optimal patient outcomes.

## Reliability You Can Trust

When a Code Blue event is invoked in your facility, a relay/pulse is sent from your Code Blue system to the timer, triggering it to begin counting up. A Code Blue event takes priority over any other timing task - however other tasks will run in the background until the Code Blue function is stopped. The included switch control allows the user to operate the timer in multiple modes during a Code Blue event.

## Product Features

- Available in 120 VAC or 24 VAC input
- Multi-functional: Code Blue Timer, Clock, Count-Up or Count Down Timer
- Highly visible, 7-segment LED digits
- Three display dimmer options: 75%, 50% and 25%
- Includes Switch Control with 14' (4.27m) cable
- Available with red or green digits\*

LEVO SERIES CODE BLUE TIMER WITH 2.5" DIGITS	
6-Digit	Description
XRA7A202C	4° Slope Bracket, 120 VAC, 10' (3.0m) cord with plug
XRA7A419C	18° Slope Bracket, 120 VAC, 10' (3.0m) cord with plug
XRA2Y202C	4° Slope Bracket, 24 VAC, 10" (25cm) cord with pigtail
XRA2Y419C	18° Slope Bracket, 24 VAC, 10" (25cm) cord with pigtail

LEVO SERIES CODE BLUE TIMER WITH 4" DIGITS	
6-Digit	Description
XRA7A203C	4° Slope Bracket, 120 VAC, 10' (3.0m) cord with plug
XRA2Y203C	4° Slope Bracket, 24 VAC, 10" (25cm) cord with pigtail

LEVO SERIES FLUSH-MOUNT CODE BLUE TIMER WITH 2.5" DIGITS	
6-Digit	Description
XRA7Y202CF-1	30" (76cm) cord with pigtail
XRA2Y202CF	24 VAC, 10" (25cm) cord with pigtail

\* Add a "G" after the item number for green LED models  
Example: XRA7A202CG OR XRA7Y419CG-1

## DUAL CLOCK BRACKET KIT

Any two surface-mount digital clocks can be mounted back-to-back to provide greater visibility in hallways and larger areas. Select the correct Dual Clock Bracket Kit for your application below.

DUAL CLOCK BRACKET KIT		
Mount	2", 6-Digit	4", 6-Digit
Ceiling	26CBRK	4XBRK
Wall	26WBRK	NA



Surface-Mount Timer



Flush-Mount Timer  
Includes clock, junction box and face plate.



Wall Mount Timer



Ceiling Mount Timer

## CODE BLUE TIMER SPECIFICATIONS:

- 7-segment LED digits
- 12- or 24-hour time display
- PM indicator light
- Alternating time and date display option
- LED dimmer option (75%, 50%, 25%)
- Code Blue input range: 5-120 VAC or DC
- Operating temperature range: 32°-194°F (0°-35°C)
- Storage temperature range: -20°-185°F (-29°-85°C)

### Power Supplies


- 120 VAC (100-240)/ 50-60 cycle, 10' (3.0m) cord with plug, UL/cUL listed
- 24 VAC (18-28), 10" (25cm) cord with pigtail

### Audible Tone Option

- Only on the count-up and count-down timer function
- Frequency: 3KHz +/-0.5KHz


## SWITCH CONTROL FOR CODE BLUE TIMERS SPECIFICATIONS:

- Allows the user to run, hold or reset the Code BlueTimer
- Designed to fit inside a single gang box (not included)
- Membrane switch and wall plate clean easily and resist common cleaners and disinfectants



### CODE BLUE TIMER DIMENSIONS


Clock Type	Weight	Height	Width	Depth
		A	B	C
2.5" (6.4cm), 6-digit	2.0 lbs. (0.9 kg)	5.0" (12.7cm)	13.8" (34.9cm)	2.2" (5.6cm)
4" (10.16cm), 6-digit	4.6 lbs. (2.1 kg)	8.0" (20.3cm)	23.3" (59.2cm)	2.4" (6.1cm)



### DUAL-MOUNT DIMENSIONS


Clock Type	Width from Wall	Height from Ceiling	Depth of Two Clocks
	A	B	C
Dual 2.5" (6.4cm), 6-digit	16.8" (42.7cm)	8.0" (20.3cm)	5.9" (15.0cm)
Dual 4" (10.16cm), 6-digit	26.3" (66.8cm)	11.0" (27.9cm)	6.3" (16.0cm)

Note: Dual mount clocks are shipped disassembled to simplify installation.



### CODE BLUE FLUSH-MOUNT TIMER DIMENSIONS

Clock Type	Weight	Width	Height	Depth
		A	B	C
2.5" (6.4cm), 6-digit	2.0 lbs. (0.9 kg)	16.8" (42.7cm)	6.5" (16.5cm)	3.4" (8.6cm)



When ordering for new construction projects, the junction boxes for flush-mount installation may be ordered to ship in advance of clocks. Please request special shipping and provide dates when ordering.

To Learn More:

Call 800.537.0464

Email: [info@primexinc.com](mailto:info@primexinc.com)

[primexinc.com](http://primexinc.com)